

FLUID HEAT TRANSFER SYSTEMS (Continued)

MODEL NUMBER	kw	BTU/HR OUTPUT	WATT DENSITY W/SQ. IN.	PUMP GPM	PUMP HP	PIPING CONNECTION	SYSTEM VOLUME (GALLONS)*	LENGTH	WIDTH	HEIGHT	APPROX. NET WEIGHT EMPTY
OHTS-10	10	34,120	15	20	3	1½"	7	78	39	72	1225
OHTS-15	15	51,180	15	20	3	1½"	8	90	39	72	1325
OHTS-20	20	68,240	15	20	3	1½"	13	78	39	72	1325
OHTS-30	30	102,360	15	20	3	1½"	16	90	39	72	1430
OHTS-40	40	136,480	15	50	7½	2"	23	82	39	80	1430
OHTS-50	50	170,600	15	50	7½	2"	25	90	39	80	1480
OHTS-60	60	204,720	15	50	7½	2"	27	96	39	80	1580
OHTS-80	80	272,690	15	90	10	2"	46	96	51	84	1830
OHTS-100	100	341,200	15	90	10	2"	48	102	51	84	1950
OHTS-120	120	409,440	15	90	10	2"	50	102	51	84	2050
OHTS-150	150	511,800	15	150	20	3"	80	108	56	90	2250
OHTS-180	180	614,160	15	150	20	3"	83	108	56	90	2350
OHTS-200	200	682,400	15	150	20	3"	84	108	56	90	2450
OHTS-225	225	767,700	12	150	20	3"	125	136	56	90	2750
OHTS-250	250	853,000	12	250	30	4"	144	156	56	90	3075
OHTS-300	300	1,023,600	12	250	30	4"	157	108	63	90	3375
OHTS-360	360	1,228,320	12	250	30	4"	160	108	63	90	3575
OHTS-400	400	1,364,800	12	350	40	4"	198	126	63	90	3775
OHTS-450	450	1,535,400	12	350	40	4"	243	138	63	90	3975
OHTS-500	500	1,706,000	12	350	40	4"	282	156	63	90	4275

* System volume excludes expansion tank.